Sisal for Square or Round Bales

Brazilian Gold

Our Brazilian represents premium-quality sisal twines by COSIBRA, Brazil's most experienced twine manufacturer.

- Extra-long fibers for consistent trouble-free baling, uniformity, and true length
- High tensile and knot strength
- Specially treated to resist rodents and insects
- Biodegradable

Square bales

9,000 ft. approx. 350 lbs tensile 40 lbs./bale

7,200 ft. approx. 425 lbs tensile 40 lbs./bale

Round bales

16,000 ft. approx. 180 lbs tensile 40 lbs./bale

Stretch Wrap for Round Balers

Manufactured using only quality virgin materials, these products contain special ultraviolet inhibitors to prolong the life of wrapped bales.

Width	Length	Thickness
500 mm (20 in.)	1800 M (5,905 ft.)	1.0 mil
750 mm (30 in.)	1500 M (4,920 ft.)	1.0 mil
750 mm (30 in.)	1250 M (4,100 ft.)	1.2 mil
750 mm (30 in.)	1000 M (3,280 ft.)	1.5 mil
750 mm (30 in.)	1500 M (4,920 ft.)	5 & 6 layers (1.0 mil))

*Stretch Color - White (other size and color available upon request).





11/2016

Tama Canada Ltd-Ltée 1480 Sandhill Drive, unit 9B Ancaster ON L9G 4V5 Phone: (905) 639-4555 Toll Free: 1-877-690-4442 Fax: 1-877-690-4442 www.tamacanada.ca



The Right Product For Your Baling Needs

Performance. Selection. Availability.



Netwrap for Round Bales claas rollatex pro



ROLLATEX PRO is produced with CLAAS COVERED[™] technology, a breakthrough which allows full bale coverage, from one edge of the bale to the other, giving a perfect shoulder-free shape to the bale.

Longer rolls save you money and time by allowing you to bale longer between roll changes.

- Full width wrapping. For a neater, more transportable bale.
- Left-right indicator. Helps you to load the roll of net into the baler correctly every time plus, when you get ready to unroll the bale at feeding time, it helps to guide you into the correct position.
- Red End Warning. A red stripe on the last 7 bales warns when roll is coming to the end.
- Carry Handles. Allowing easier and safer handling.
- Weather Resistant. Minimizes loss due to spoilage.
- Easier to remove and dispose of than conventional twine

EnterNet feature - A special pre-fitted tag holds the beginning of the net and helps thread the net through the baler.



Round Bales

48" (122 cm) x 14,700 ft (4500m)




High Performance Twine for QUADRANT Balers

CLAAS QUADOTEX 3400

- Achieve the full performance of the QUADRANT 3400/3300 balers
- Especially developed for the CLAAS single-knot system
- Perfectly adapted to the knotters and the twine locations of the QUADRANT balers
- Optimum relation between runnage and knot resistance
- Smooth operation with limited wear on the baler
- High resistance to demanding climate and UV conditions

Length	Weight	Linear Strength	Knot Strength
3848 ft	25.35 lbs	882 lbs	617 lbs
(1173m)	(11.5 kg)	(400 kg)	(280 kg)

*Color: light green



Degradable Polypropylene for Round Bales

Clearfield™

Designed to give user the benefits of both plastic and sisal twines

- Combines the unique benefits of plastic and sisal twines in one product.
- Lasts longer than sisal twine, but unlike plastic twine will eventually decompose.
- Yellow color for high visibility.

Round bales

20,000 ft. 110 lbs tensile in one spool

Polypropylene Twine for Square or Round Bales

Balebind™

- Contains special UV light inhibitors
- Twine runs trouble-free in baler
- Always uniform consistency

Small square bales

Twine type	Length	Knot strength
Balebind 7,200	7,200 ft. (2-spool pack)	170 lbs
Balebind 9,000	9,000 ft. (2-spool pack)	140 lbs
Balebind 9,600	9,600 ft. (2-spool pack)	210 lbs
Balebind 12,000	12,000 ft. (2-spool pack)	190 lbs
Large square bales		
Balebind 4,000	4,000 ft. (Single-spool pack)	450 lbs
Round bales		
Twine type	Length	Tensile strength
Balebind 40,000	40,000 ft. (2-spool pack)	110 lbs
Balebind 28,000	28,000 ft. (2-spool pack)	110 lbs

BT-450

TamaTwine+

- Reduces your costs and increases your baler's potential.
- Combines the strength of "traditional" 450 twine, with a 10% increase in length.

Large square bales

Twine type	Length	Knot strength
Tama LSB	4,400 ft. (Single-spool)	450 lbs



